

CHEMLUBE® NGC SERIES

NATURAL GAS COMPRESSOR LUBRICANTS

Applications:

Chemlube NGC Series are fully synthetic blends, formulated utilizing superior base stock fortified with a proprietary additive package. Chemlube NGC 100 and 150 were designed to inhibit the formation of varnish and carbon build-up and also will protect against thermal break down and extend oxidative stability. They provide extended equipment life and decrease lubricant drain intervals.

Typical Industrial Applications:

- Rotary Screw Compressors
- Rotary Vane Compressors
- Centrifugal Compressors
- Reciprocating Compressors

Performance Benefits:

- Excellent film strength
- Good compatibility with most base oils
- Good oxidative stability
- High flash point

TYPICAL PROPERTIES	TEST METHOD	Chemlube NGC 100	Chemlube NGC 150
ISO Grade	ASTM D2422	100	150
Viscosity @ 40°C,cSt	ASTM D445	97.3	151
Viscosity @ 100°C,cSt	ASTM D445	16.0	18.1
Viscosity Index	ASTM D2270	178	139
Flash Point, °C/°F	ASTM D92	252/486	252/486
Pour Point, °C/°F	ASTM D97	-36/-33	-36/-33
Specific Gravity	ASTM D1298	0.88	0.88

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE
IN
USA



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com