

PGWI SERIES PREMIUM PAG-BASED LUBRICANTS

Applications:

The PGWI Series are fully synthetic lubricants formulated with superior polyalkylene glycol (PAG)-based oils. These premium lubricants are designed for use in compressors and vacuum pumps compressing polar gases, such as NH₃, CO₂, and propane. They offer excellent rust resistance and are excellent in wet gas compression. The PGWI Series yield a compressor service life of 8,000 – 10,000 hours under good operating conditions.

Typical Industrial Applications:

- Rotary Screw Compressors
- Rotary Vane Compressors
- Centrifugal Compressors
- Reciprocating Compressors
- Vacuum Pump

Performance Benefits:

- Resists hydrocarbon washout/dilution
- Extended drain life
- Reduced sludge and deposit formation
- Excellent oxidative and thermal stability

PGWI

TYPICAL PROPERTIES	TEST METHOD	PGWI 46	PGWI 68	PGWI 100	PGWI 150
ISO Grade	---	46	68	100	150
Viscosity @ 40°C,cSt	ASTM D445	46	69	106	154
Viscosity @ 100°C,cSt	ASTM D445	9.4	12.9	18.9	25.7
Viscosity Index	ASTM D2270	191	193	195	195
Flash Point, °C/°F	ASTM D92	210/415	230/445	230/445	230/445
Pour Point, °C/°F	ASTM D97	-50/-60	-40/-40	-40/-40	-38/-36
FZG Load Stage	DIN-51354	11	11	11	12
Four ball wear-40Kg.,1200rpm, 1 hr@75°C, Scar Diameter, mm	ASTM D4172	0.53	0.52	0.51	0.51
Specific Gravity	ASTM D1298	0.98	0.98	0.98	0.99

Caution: Not compatible with petroleum oils and synthetic hydrocarbons

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE
IN
USA



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com